

LED EcoMax DC 12V Strip


Features

- Broad beam angle
- High quality
- Energy efficient

Benefits

- Simple and safe installation
- Durable for indoor use

Application



Specification

Product Description	Power (W/m)	Lumen (lm/m)	Beam Angle (°)	CCT (K)	Lifetime (hrs)	Energy Level
LED-E-12/2835-01-6W/60-824-Bare-5M	6W/M	580	120°	2400K	15000	A+
LED-E-12/2835-01-6W/60-827-Bare-5M	6W/M	620	120°	2700K	15000	A+
LED-E-12/2835-01-6W/60-830-Bare-5M	6W/M	650	120°	3000K	15000	A+
LED-E-12/2835-01-6W/60-840-Bare-5M	6W/M	680	120°	4000K	15000	A+
LED-E-12/2835-01-6W/60-865-Bare-5M	6W/M	690	120°	6500K	15000	A+
LED-E-12/2835-01-6W/60-824-Tube-5M	6W/M	550	120°	2400K	15000	A+
LED-E-12/2835-01-6W/60-827-Tube-5M	6W/M	590	120°	2700K	15000	A+
LED-E-12/2835-01-6W/60-830-Tube-5M	6W/M	620	120°	3000K	15000	A+
LED-E-12/2835-01-6W/60-840-Tube-5M	6W/M	650	120°	4000K	15000	A+
LED-E-12/2835-01-6W/60-865-Tube-5M	6W/M	660	120°	6500K	15000	A+
LED-LV-STRIP-12V-U-4W-3000K-BL+DRIVER	4W/M	500	120°	3000K	15000	A+
LED-LV-STRIP-12V-U-4W-6500K-BL+DRIVER	4W/M	500	120°	6500K	15000	A+
LED-LV-STRIP-12V-U-12W-3000K	12W/M	1200	120°	3000K	15000	A+
LED-LV-STRIP-12V-U-12W-6500K	12W/M	1200	120°	6500K	15000	A+

Application Conditions	
IP	20
Operating Temperature	-10-45°C
Application Temperature	25°C
Storage Environment	-25-50°C

Mechanical and Finishing Properties	
Optical Material	PVC
Housing Material	Copper
Finishing Colour	White

Electrical supply	
Frequency (Hz)	50/60Hz
Voltage (V)	12V
AC/DC	DC



Packaging Information

Item Description	Single Box(1pc/box)		Packaging Unit			Remark
	Dimensions(mm) (LxWxH)	Gross Weight (kg)	Dimensions(mm) (LxWxH)	Gross Weight (kg)	Packing Qty (pcs/unit)	
LED-E-12/2835-01-6W/60-824-Bare-5M	5000*8*2.5	0.06	460*230*380	8	80M	4*20 roll (5M/roll)
LED-E-12/2835-01-6W/60-827-Bare-5M	5000*8*2.5	0.06	460*230*380	8	80M	4*20 roll (5M/roll)
LED-E-12/2835-01-6W/60-830-Bare-5M	5000*8*2.5	0.06	460*230*380	8	80M	4*20 roll (5M/roll)
LED-E-12/2835-01-6W/60-840-Bare-5M	5000*8*2.5	0.06	460*230*380	8	80M	4*20 roll (5M/roll)
LED-E-12/2835-01-6W/60-865-Bare-5M	5000*8*2.5	0.06	460*230*380	8	80M	4*20 roll (5M/roll)
LED-E-12/2835-01-6W/60-824-Tube-5M	5000*10*4	0.21	465*305*270	10.4	40M	2*20 roll (5M/roll)
LED-E-12/2835-01-6W/60-827-Tube-5M	5000*10*4	0.21	465*305*270	10.4	40M	2*20 roll (5M/roll)
LED-E-12/2835-01-6W/60-830-Tube-5M	5000*10*4	0.21	465*305*270	10.4	40M	2*20 roll (5M/roll)
LED-E-12/2835-01-6W/60-840-Tube-5M	5000*10*4	0.21	465*305*270	10.4	40M	2*20 roll (5M/roll)
LED-E-12/2835-01-6W/60-865-Tube-5M	5000*10*4	0.21	465*305*270	10.4	40M	2*20 roll (5M/roll)
LED-LV-STRIP-12V-U-4W-3000K-BL+DRIVER	5000*8*1.3	0.26	445*370*230	5.6	20	5M strip and driver
LED-LV-STRIP-12V-U-4W-6500K-BL+DRIVER	5000*8*1.3	0.26	445*370*230	5.6	20	5M strip and driver
LED-LV-STRIP-12V-U-12W-3000K	5000*8*1.3	0.08	460*230*390	7.2	80	only 5M strip
LED-LV-STRIP-12V-U-12W-6500K	5000*8*1.3	0.08	460*230*390	7.2	80	only 5M strip
LED-E-12/2835-01-Input connector-4A	/	0.002	285*220*245	24	12000	120*100pcs
LED-E-12/2835-01-Middle connector-4A	/	0.001	285*220*245	32	32000	320*100pcs
LED-E-12/2835-01-Jumper connector-4A	/	0.003	285*220*245	18	6000	60*100pcs
LED-E-Strip-Driver-30W-DC12V	194*43*43	0.208	250*225*170	4.76	20	20pcs
LED-E-Strip-Driver-60W-DC12V	194*43*43	0.264	250*225*170	6	20	20pcs

Dimensional Drawing



	6W(Tube)	6W(Bare)	4/12W
A (mm)	5000	5000	5000
B (mm)	10	8	8
C (mm)	4	2.5	1.3